

TECHNICAL SPECIFICATIONS 800 SERIES BALLISTIC INSERTS

# 3810 LEVEL III+ · Stand Alone · NIJ Certified



**THICKNESS: 0.98 in (25 mm), AREAL DENSITY: 5.52 lb/ft<sup>2</sup>**

**SHOOTER CUT - MULTI CURVE - TORSO PLATES**

PART NUMBER	WIDTH x LENGTH	WEIGHT
<b>3810-SH-MC-L</b>	10.0 x 12.0 in (254 x 305 mm)	3.9 lb (1.8 kg)
<b>3810-SH-MC-S</b>	8.0 x 10.0 in (203 x 254 mm)	2.5 lb (1.2 kg)

**SAPI CUT - MULTI CURVE - TORSO PLATES**

PART NUMBER	WIDTH x LENGTH	WEIGHT
<b>3810-SA-MC-XL</b>	11.00 x 14.00 in (279 x 356 mm)	5.4 lb (2.5 kg)
<b>3810-SA-MC-L</b>	10.25 x 13.25 in (260 x 337 mm)	4.7 lb (2.1 kg)
<b>3810-SA-MC-M</b>	9.50 x 12.50 in (241 x 318 mm)	4.1 lb (1.8 kg)
<b>3810-SA-MC-S</b>	8.75 x 11.75 in (222 x 298 mm)	3.5 lb (1.6 kg)



Full Cut option available by special order only.  
Please contact your Hesco Armor representative for more information.

**Manufacturing Tolerances:**

Thickness dimensions are ±1/8 in (± 3 mm). Width and length dimensions are +0.00 to -0.25 in (+0.00 to -6 mm). All weights are ± 5%.

**THREAT PERFORMANCE MATRIX:**  
**3810**

	5.56 x 45 mm - M193 Max Velocity 2280 ft/s (700 m/s)		7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)		7.62 x 51 mm - M80 * Max Velocity 2910 ft/s (896 m/s)		7.62 x 63 mm - JSP Max Velocity 2794 ft/s (852 m/s)		5.56 x 45 mm - M855 / S5109 Max Velocity 2950 ft/s (900 m/s)		7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	
	LEAD CORE		LEAD CORE		LEAD CORE		LEAD CORE		MILD STEEL CORE		MILD STEEL CORE	
<b>3810-SH-MC-L</b>	6	6	6	2	6	3	6	3	3	3	3	3
<b>3810-SH-MC-S</b>	3	3	3	1	3	3	3	3	3	3	3	3
<b>3810-SA-MC-XL</b>	6	6	6	2	6	3	6	3	3	3	3	3
<b>3810-SA-MC-L</b>	6	6	6	2	6	3	6	3	3	3	3	3
<b>3810-SA-MC-M</b>	6	6	6	2	6	3	6	3	3	3	3	3
<b>3810-SA-MC-S</b>	3	3	3	1	3	3	3	3	3	3	3	3

\* NIJ Level III Certification Threat

**Hesco Testing Protocol**

NIJ Certification of hard armor requires submission of 10" x 12" test plates which must demonstrate the ability to defeat specific rounds tested to a valid NIJ shot pattern, after exposure to a stringent conditioning protocol to simulate aging and wear. Level III requires six rounds of 7.62 x 51 mm - M80 per plate.

Hesco holds itself to a higher standard by publishing the minimum number of shots that each size plate can be expected to defeat under similar NIJ testing methods, as well as listing many additional threats not addressed under the NIJ Certification process. The minimum number of shots are shown in the Threat Performance Matrix.

**General Information**

Advanced ceramic/Spectra® design. Mult shot rated on selected threats. Light AP protection including 5.56 x 45 M855. Water repellant polyurethane coated CORDURA® fabric finish. Made in the U.S.A.

**NIJ Standard-0101.06**

Tested and verified to meet or exceed ballistic resistance as specified under NIJ Standard-0101.06 plus Special Rifle Threats validated.

**Export Control Advisory**

Model 3810 (ECCN 1A613.d.2) is subject to the Export Administration Regulations (EAR). It may not be sold or otherwise provided to any non-U.S. Person and/or exported or re-exported without a valid U.S. Department of Commerce BIS export license, or applicable EAR license Exception.

**Hesco Armor, Inc.**  
2210 Port Industrial Road  
Aberdeen WA 98520, United States  
Telephone: +1 360 637 6867  
Email: support@hesco.com

**Disclaimer:** The information contained in this document is intended solely to provide general guidance. The right is reserved to make changes to this document without notice at any time. Nothing in this document (i) constitutes an offer, representation, warranty, term or condition or (ii) is a substitute for the need to employ adequate independent technical expertise and judgment.

**Patents and Trademarks:** HESCO® products are subject to patents and/or patent applications in territories around the world. HESCO® is a registered trademark of Hesco Bastion Ltd and its affiliates ("Hesco") around the world. Other trademarks also apply. For full details, please go to: [www.hesco.com/legal\\_notice](http://www.hesco.com/legal_notice)

**Quality Standards:** Hesco operates a Quality Management System certified to ISO 9001:2015/BA 9000:2016. Approved Certificate Number: C2019-01385. AQAP 2110 Conformance, Approved Certificate Number: C2019-01645.

This material is subject to copyright protection. Copyright © 2023 Hesco. All rights reserved.

[hesco.com](http://hesco.com)